



Features

- ✓ Digital inputs and outputs

Input / Output module digital for 300

Digital mix modules for the 300 series

The module has 8 inputs and 8 outputs.

General information

Order number	700-323-1BH01
Article name	DEA 300, DC 24 V, 0.5 A, 8 inputs (DC 24 V)/8 outputs (DC 24 V, 0.5 A)
Scope of delivery	DEA 300, DC 24 V, 0.5 A, 8 inputs (DC 24 V)/8 outputs (DC 24 V, 0.5 A)
Dimensions (DxWxH)	116 x 40 x 125 mm
Weight	Approx. 220g
Number of inputs	8
Number of outputs	8
Rated value	0.5 A
Short-circuit protection	Electronic
Inductive cutoff voltage limit	-48 V

Power dissipation (nominal operation)	typ. 3.5 W
Front connectors	20-pin

Input voltage

For signal "0"	-3 ... +5 V
For signal "1"	+13 ... +30 V
Rated value	24 V DC
Input current for signal "1"	typ. 7 mA
Delay time	1.2 ... 4.8 ms
Can accommodate 2-wire initiator	Yes

Cable length

Unshielded	600 m
Shielded	1000 m

Electrical isolation

from the backplane bus	Yes (optocoupler)
in groups to	8

Supply voltage UP, US

Rated value	24 V DC
Ripple USS	max. 3.6 V
Permissible range (with ripple)	+20 ... +30 V

Current draw

Internal (backplane bus)	typ. 55 mA
External (from +24 V/L+)	Max. 60 mA

Ambient conditions

Ambient temperature	0 °C ... +60 °C
Transport and storage temperature	-25 °C ... +75 °C
Pollution degree	2
Protection rating	IP20
Approvals	CE

