



Features

- ✓ Gain 4 dBi
- ✓ 2 x 5 m Cable length
- ✓ SMA male connector
- ✓ Indoor and outdoor

Cellular Antennas MiMo Wall, 4 dBi

REX industrial routers with an integrated cellular modem require an LTE antenna.

For radio reception, a suitable antenna must be screwed to at least the SMA socket of the router "MAIN" (ANT 2).

MiMo wall antenna with two cables. In order to improve the 4G data throughput, a second antenna terminal is available on the REX 100 LTE router with the SMA socket "Rx" (ANT1). If you would only like to install one antenna, we recommend the MiMo wall antenna, as it already contains two antennas in one housing. Our technical sales is happy to answer any questions you may have regarding the various antennas.

General information

Order number	700-751-ANT35
Article name	MiMo wall antenna, GSM/UMTS/LTE, 4 dBi, 2x 5 m cable, SMA male connectors
Scope of delivery	MiMo wall antenna, incl. cable
Radio networks	LTE 800 GSM 900 GSM 1800, UMTS LTE 2600
Frequency range	800–960 MHz 1710–2500 MHz 2500–2700 MHz
Radiation pattern	Omni-directional
Gain	2 dBi 5 dBi 4 dBi
VSWR	< 2 : 1

Max. input power	20 W
Impedance	50 Ω
Cable length	5 m, CS29 Coax
Connector type	2x SMA (m)
Antenna	155 mm
Height	186 mm