



Features

- ✓ Remote access to Ethernet-enabled devices such. PLC, HMI, IP camera
- ✓ WAN, WIFI, 3G or LTE variants available
- ✓ WAN interface for fail-over operation (3G, LTE and Wifi)
- ✓ Space saving and compact
- ✓ Integrated firewall
- ✓ Integrated 4-port LAN switch
- ✓ Digital inputs and outputs for connection establishment, status display and alarm
- ✓ Easy and fast configuration via the myREX24 VPN portal
- ✓ Read, visualize and log data from PLC
- ✓ Direct connection of S7-MPI / PROFIBUS devices
- ✓ Free S7-MPI / PROFIBUS driver
- ✓ Remote control of remote devices via Internet (RS232)
- ✓ Remotely maintain USB devices over the Internet

Industrial-Router REX 250 with WAN LTE (EU & Asia)

More than just remote maintenance! With REX industrial routers, you can access all components in your machine. Set up simple alerts and use your smartphone to access services within the system - such as websites or VNC-enabled components.

The REX 250 routers are designed for operation in conjunction with the myREX24 V2 portal: The complete parameterization and remote maintenance is carried out via the portal. In addition to remote maintenance, the REX 250 routers can also read data from the PLC, visualize and generate alarms. For remote maintenance and data transmission, the industrial router uses an encrypted VPN tunnel based on the secure OpenVPN protocol.

The REX 250 routers also enable remote maintenance and data access to PLCs via an MPI / PROFIBUS and via an RS232 interface.

With the 4 digital inputs, alarms can be sent via SMS and email via the myREX24 V2 Portal. The 2 digital outputs can change the system states of the router, e.g. with a lamp on the control cabinet, or can be activated via the portal.

The USB host interface available on all devices enables the connection of USB device devices (eg programming interface of a drive) via the remote maintenance tunnel (USB-over-IP).

The REX 250 LTE has an LTE modem, which connects to the myREX24 V2 portal. The WAN interface, which is also available, can form a fail-over network in conjunction with the 4G modem. The integrated 4-port switch can be used to connect the Ethernet nodes of the machine to the router on the available RJ45 ports.

The LTE modem used supports use in Europe and Asia. For using the router in North America, please use the "REX 100 with LTE modem for North America" (700-875-LTE11). In general, before using an LTE router, please compare the LTE frequency bands of the selected device with the supported frequency

bands of the provider in the country of use. We will be happy to help you.

Please use a standard cell phone data plan when selecting a cell phone contract. Please avoid IoT tariffs, as these are often only designed for small data volumes or transmission speeds.

General information

Order number	700-878-LTE02
Article name	REX 250 LTE, 4 x LAN (switch)/1 x WAN/1 x LTE modem
Scope of delivery	REX 250 LTE, Quick Start Guide
Dimensions (DxWxH)	35 x 100 x 73 mm
Weight	Approx. 250 g
Status indicator	8 LEDs, function status
	10 LEDs, Ethernet status
Voltage supply	24 V DC, 18... 28 V DC
Current draw	max. 90 mA at DC 24 V

I/O

Digital inputs	4x DIN EN 61131-2 Type 3
Digital outputs	2x max. 0.5 A for each output

GSM modem

GSM-Modem	Multiband GSM/GPRS/WCDMA/LTE Data Interface
Antenna terminal	SMA socket (Male thread)
SIM card type	Standard SIM 1.8 V/3 V
GSM frequency bands	GSM/GPRS/EDGE: 850, 900, 1800, 1900
UMTS frequency bands	B1 [from HW x-x-3B], B2 [up to HW x-x-3A], B3 [from HW x-x-3B], B8
Transmit power	Class 1, E2, 3, 4
Data transmission rate	HSxPA+ (Uplink max. 5.76 Mbps Downlink max. 42.0 Mbps)
	LTE (Uplink max. 50 Mbps Downlink max. 150 Mbps)
LTE frequency bands (MHz)	B1, B3, B7, B8, B20 [only HW x-x-3A], B28A [from HW x-x-3B]

WAN interface

Number	1
Type	10-Base-T/100-Base-T
Connection	RJ45 socket
Transmission rate	10/100 Mbps

LAN interface

Number	4
Type	10-Base-T/100-Base-T
Connection	RJ45 socket
Transmission rate	10/100 Mbps

USB interface

Number	1
Protocol	USB 2.0 host
Connection	USB-A port

Serial Interface

Type	RS-232/422/485 (software switchable)
Protocol	transparent access via virtual COM port
Transmission rate	300 bauds ... 115 k bauds

PROFIBUS interface

Transmission rate	up to 12 Mbps
Interface	RS-232/485 (software switchable)
Connection	Socket, SUB-D, 9-pin

Ambient conditions

Ambient temperature	-40 °C ... +75°C
Transport and storage temperature	-40 °C ... +85 °C
Relative air humidity	95% r. H. without condensation
Pollution degree	2
Protection rating	IP20
Approvals	CE

As of: 7 - 2026