



Features

- ✓ 110–230 V AC input voltage
- ✓ Each channel has its own individual neutral conductor terminal
- ✓ A blue LED indicates the module's operating status
- ✓ Green LEDs (one for each input) indicate the input status
- ✓ 4 inputs, electrically isolated from the backplane bus

Digital input module, AC 230 V, per channel N 4x

Im Lieferumfang sind bereits der passende Frontstecker für die Verkabelung und ein Basismodul enthalten. Das Modul verfügt über 16 digitale Eingänge in m-lesender Ausführung.

The scope of delivery already includes the appropriate front connector for the cabling and a base module. The module has 4 digital inputs for 230V AC.

General information

Order number	600-211-0BD01
Article name	DI 4x AC 230 V, per channel N, type 1
Scope of delivery	DI 4x AC 230 V, per channel N, type 1
Dimensions (DxWxH)	110 x 14 x 73 mm
Weight	Approx. 70 g
Number of inputs	4
Power dissipation	Max. 7.6 W
Input characteristic curve	Type 1, EN 61131-2
Input frequency	50 Hz / 60 Hz
Hot-swap capable	Yes

Hot-swap capable	Yes
------------------	-----

Electrical isolation

from the backplane bus	Yes
------------------------	-----

Between the channels	Yes
----------------------	-----

Current draw

External	Max. 0 mA
----------	-----------

Internal	Max. 22 mA
----------	------------

Input voltage

For signal "0"	0 V ... 40 V
----------------	--------------

For signal "1"	79 V ... 253 V
----------------	----------------

For signal "1"	79 V ... 253 V
----------------	----------------

Ambient conditions

Ambient temperature	0 °C ... +60 °C
---------------------	-----------------

Transport and storage temperature	-20 °C ... +80 °C
-----------------------------------	-------------------

Relative air humidity	95 % r H without condensation
-----------------------	-------------------------------

Protection rating	IP 20
-------------------	-------

Certifications	CE, UL
----------------	--------

UL

Surrounding Air Temperature	0 °C ... +60°C
-----------------------------	----------------

Pollution degree	2
------------------	---

CE

Noise immunity	DIN EN 61000-6-2 "EMC Immunity"
----------------	---------------------------------

Interference emission	DIN EN 61000-6-4 "EMC Emission"
-----------------------	---------------------------------

Vibration and shock resistance	DIN EN 60068-2-6:2008 „Vibration“, DIN EN 60068-2-27:2010 „Shock“
--------------------------------	---

As of: 7 - 2026